

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A molecular detector capable of detecting molecules in solution comprising:

a solution reservoir;

at least one biofunctionalized nanometer-scale mechanical resonator disposed within the reservoir;

a driver element adapted to mechanically displace the mechanical resonator at a one or more frequencies; and

a detector in signal communication with the at least one resonator for measuring a damping of resonance motion of the resonator driven by the driver element in response to a molecular binding event on the resonator.

2. (Original) A molecular detector as described in claim 1, wherein the at least one resonator comprises a resonator selected from the group consisting of: vibrational resonators, rotational resonators, torsional resonators and composite resonators.

3. (Original) A molecular detector as described in claim 1, wherein the at least one resonator is a notched vibrational cantilever.

4. (Original) A molecular detector as described in claim 1, wherein the at least one resonator is biofunctionalized with a receptor.

5. (Original) A molecular detector as described in claim 4, further comprising a substrate disposed within the reservoir and adjacent to the at least one resonator, wherein the substrate is biofunctionalized with a ligand capable of molecular interaction with the receptor.

6. (Withdrawn) A molecular detector as described in claim 4, further comprising a substrate disposed within the reservoir and adjacent to the at least one resonator, wherein the substrate is biofunctionalized with a receptor capable of molecular interaction with a ligand wherein the ligand is capable of molecular interaction with the receptor on the resonator.

7. (Withdrawn) A molecular detector as described in claim 1, comprising at least two resonators arranged adjacent to one another, wherein at least one of the resonators is biofunctionalized with a receptor to form a receptor resonator and at least one of the resonators adjacent to the receptor resonator is biofunctionalized with a ligand capable of molecular interaction with the receptor.

8. (Withdrawn) A molecular detector as described in claim 1, comprising at least one additional resonator arranged adjacent to the biofunctionalized nanometer-scale mechanical resonator within the reservoir,

wherein at least one of the resonators is a driver resonator comprising a driving element capable of mechanical displacing the driver resonator at a chosen frequency, wherein the driver resonator is biofunctionalized with a receptor;

and at least one of the resonators adjacent to the driver resonator is biofunctionalized with a ligand capable of molecular interaction with the receptor on the driver resonator.

9. (Withdrawn) A molecular detector as described in claim 1, comprising at least two resonators arranged adjacent to the biofunctionalized nanometer-scale mechanical resonator within the reservoir,

wherein at least one of the resonators is a driver resonator comprising a driving element capable of mechanically displacing the first driver resonator at a chosen frequency;

wherein at least one of the resonators is a second driver resonator comprising a driving element capable of mechanically displacing the second driver resonator at a chosen frequency;

and at least one of the resonators is a follower resonator disposed between the two driver resonators and biofunctionalized with a ligand;

wherein the driver resonators are driven in antiphase, and wherein at least one of the driver resonators is biofunctionalized with a receptor capable of molecular interaction with the ligand on the follower resonator.

10. (Withdrawn) A molecular detector as described in claim 8 or 9 wherein the driver is a piezoelectric device.

11. (Original) A molecular detector as described in claim 1, wherein the at least one resonator is made from a material selected from the group consisting of: silicon oxide, silicon, silicon carbide and gallium arsenide.

12. (Original) A molecular detector as described in claim 1, wherein the detector is integral with the resonator.

13. (Original) A molecular detector as described in claim 1, wherein the detector is a piezoresistive transducer.

14. (Original) A molecular detector as described in claim 13, wherein the transducer is made of p+ doped silicon.

15. (Original) A molecular detector as described in claim 1, wherein the detector is an optical detector.

16. (Original) A molecular detector as described in claim 1, wherein the detector is a lock-in detector.

17. (Original) A molecular detector as described in claim 1, wherein the resonator has a thickness between about 10 nm and 1 μ m, a width between about 10nm and 1 μ m, and a length between about 1 μ m and 10 μ m.

18. (Original) A molecular detector as described in claim 1, wherein the resonator has a resonance motion vacuum frequency between about 0.1 and 12MHz.

19. (Original) A molecular detector as described in claim 1, wherein the resonator has a force constant between about 0.1mN/m and 1 N/m.

20. (Original) A molecular detector as described in claim 1, wherein the resonator has a Reynolds number between about 0.001 and 2.0.

21. (Original) A molecular detector as described in claim 1, wherein the resonator has a mass loading coefficient between about 0.3 and 11.

22. (Original) A molecular detector as described in claim 1, having a force sensitivity of about 8fN/ $\sqrt{\text{Hz}}$ or greater.

23. (Previously Presented) A molecular detector as described in claim 1, wherein the at least one resonator is biofunctionalized to detect a receptor/ligand interaction.

24. (Previously Presented) A molecular detector as described in claim 1, wherein the at least one resonator is biofunctionalized to detect DNA hybridization.

25. (Previously Presented) A molecular detector as described in claim 1, wherein the at least one resonator is biofunctionalized to detect a chemical bond.

26. (Previously Presented) A molecular detector as described in claim 1, wherein the at least one resonator is biofunctionalized to detect protein unfolding.

Claims 27-32 (Canceled).

33. (Withdrawn) A molecular detector as described in claim 1, wherein the at least one resonator is biofunctionalized with a ligand.

34. (Previously Presented) A molecular detector as described in claim 1, wherein the detector is a detector which is adapted to measure a change in damping of resonance motion of the resonator in response to a molecular binding event on the resonator.

35. (Previously Presented) A molecular detector as described in claim 1, wherein the resonator comprises a cantilever having at least two dimensions of one micron or less.

36. (Previously Presented) A molecular detector as described in claim 13, wherein the detector comprises a piezoresistive detector layer which is located on the resonator.

37. (Currently Amended) A molecular detector capable of detecting molecules in solution comprising:

a solution reservoir;

at least one first nanometer-scale mechanical resonator which is disposed within the reservoir, wherein the at least one first resonator is biofunctionalized with a receptor or a ligand;

a driver element adapted to mechanically displace the mechanical resonator at a one or more frequencies

a substrate or a second mechanical resonator which is disposed within the reservoir, wherein the substrate or the second resonator is biofunctionalized with another one of a receptor or a ligand which is capable of molecular interaction with the receptor or ligand on the at least one first resonator; and

a detector in signal communication with the at least one first resonator for measuring a damping of resonance motion of the resonator driven by the driver element in response to a molecular binding between the at least one first resonator and the substrate or the second mechanical resonator.

38. (Withdrawn) A molecular detector as described in claim 37, wherein the detector is a detector which is adapted to measure a damping of resonance motion of the first resonator in response to a binding event between the receptor or ligand on the first resonator and another one of a receptor or ligand on the substrate or the second resonator such that the first resonator is tethered to the substrate or to the second resonator.

39. (Withdrawn) A molecular detector as described in claim 38, wherein the detector comprises a piezoresistive detector layer which is located on the resonator.

40. (Previously Presented) A molecular detector as described in claim 37, wherein the substrate is disposed in the reservoir.

41. (Withdrawn) A molecular detector as described in claim 40, wherein the at least one first resonator is biofunctionalized with a ligand and the substrate is biofunctionalized with a receptor.

42. (Previously Presented) A molecular detector as described in claim 40, wherein the at least one first resonator is biofunctionalized with a receptor and the substrate is biofunctionalized with a ligand.

43. (Withdrawn) A molecular detector as described in claim 37, wherein the second resonator is disposed in the reservoir.

44. (Withdrawn) A molecular detector as described in claim 43, wherein the at least one first resonator is biofunctionalized with a ligand and the second resonator is biofunctionalized with a receptor.

45. (Withdrawn) A molecular detector as described in claim 43, wherein the at least one first resonator is biofunctionalized with a receptor and the second resonator is biofunctionalized with a ligand.

46. (Previously Presented) A molecular detector as described in claim 37, further comprising a driving element capable of mechanically displacing the first resonator at a chosen frequency.

47. (Previously Presented) A molecular detector capable of detecting molecules in solution comprising:

a solution reservoir;

at least one first nanometer-scale mechanical resonator which is disposed within the reservoir, wherein the at least one first resonator is biofunctionalized with a first receptor or a first ligand;

a substrate or a second mechanical resonator which is disposed within the reservoir, wherein the substrate or the second resonator is biofunctionalized with a second receptor or a second ligand, and wherein the first receptor or ligand and the second receptor or ligand are capable of binding to a third receptor or a third ligand in a solution such that the third receptor or ligand binds to both the first receptor or ligand and to the second receptor or ligand at a same time; and

a detector in signal communication with the at least one first resonator for measuring a mechanical displacement of the resonator.

48. (Withdrawn) A molecular detector as described in claim 47, wherein the detector is a detector which is adapted to measure a change in force constant of resonance motion of the first resonator in response to a binding event between the third receptor or

ligand and both the first and second receptors or ligands such that the first resonator is tethered to the substrate or to the second resonator.

49. (Previously Presented) A molecular detector as described in claim 47, wherein the detector comprises a piezoresistive detector layer which is located on the resonator.

50. (Previously Presented) A molecular detector as described in claim 47, wherein the substrate is disposed in the reservoir.

51. (Withdrawn) A molecular detector as described in claim 50, wherein:

the at least one first resonator is biofunctionalized with a first receptor;

the substrate is biofunctionalized with a second receptor;

the first receptor and the second receptor are capable of binding to a third ligand in a solution such that the third ligand binds to both the first receptor and the second receptor at a same time.

52. (Withdrawn) A molecular detector as described in claim 47, wherein the second resonator is disposed in the reservoir.

53. (Currently Amended) A molecular detector capable of detecting molecules in solution comprising:

a solution reservoir;

at least one biofunctionalized nanometer-scale mechanical resonator disposed within the reservoir;

a driver element adapted to mechanically displace the mechanical resonator at a one or more frequencies; and

a means for measuring a damping of resonance motion of the resonator driven
by the driver element in response to a molecular binding event on the resonator.

54. (Withdrawn) A molecular detector as described in claim 53, wherein the means for measuring comprises a means for measuring a change in damping of resonance motion of the resonator in response to a molecular binding event on the resonator.

55-60 (Cancelled).